

Double Glazed Units	Maximum Sizes	With 20mm Cavity			
	Width	Height	Maximum Square	Area	Weight
	mm	mm	mm	m ²	Kg
2*4 Float					
Annealed	1300	2100	1300*1300	2.00	40
Toughened	1400	2500	1400*1400	3.00	60
2*6 Float					
Annealed	1400	2400	1500*1500	3.00	90
Toughened	1500	2700	1500*1500	3.00	90
Laminated	1320	2140	1200*1200	2.82	85
Texture Glass Units					
All Types	1300	2100	1300*1300	2.00	40

All Triple Glazed Units	Maximum Sizes	With 2*10mm Cavities			
	Width	Height	Maximum Square	Area	Weight
	mm	mm	mm	m ²	Kg
	800	1900	1175*1175	1.52	46

All Unit Types	Minimum Size
	mm
Annealed	200*300
Toughened	300*300
Laminated	300*300

Notes

The description "Float" covers Clear, Low Iron, Low E, Self Cleaning, Tinted & most other non-texture glass types

These sizes are normal manufacturing limits for standard lead times and prices, we can supply under or oversize units on request - please ask for a cost and delivery quote

Different criteria may apply to Leaded, Georgian, Intercept & Bevelled or Stained units

Sizes are for units with 16 or 20mm aluminium or warm edge spacer bar and Hot Melt secondary seal for use in domestic window installations. Please ask for other applications